

Nom : Lubricant for chains

**1 - IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING ENTREPRISE****1.1. Product identifier**

Product name : Lubricant for chains

Product code : NL75500

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

N/A

**1.3. Details of the supplier of the safety data sheet**

Name : VAR.

Address: 19 AVENUE GUSTAVE EIFFEL

28630 GELLAINVILLE

FRANCE



Telephone: +33 (0) 2 37 33 37 10

Fax: +33 (0) 2 37 33 37 17

contact@vartools.com

<http://www.vartools.com>**Emergency telephone number : +33 (0)1.45.42.59.59.**Association/Organisation: INRS/ORFILA <http://www.centres-antipoison.net>**2 – HAZARDS IDENTIFICATION****2.1. Classification of the substance or mixture**

Directive criteria, 67/548/CE, 99/45/EC and following amendments thereof:

Properties / Symbols:

F+ Extremely flammable

Xi Irritant

N Dangerous for the environment

R Phrases:

R12 Extremely flammable.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

EC regulation criteria 1272/2008 (CLP):



Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.



Warning, Skin Irrit. 2, Causes skin irritation.



Warning, Eye Irrit. 2, Causes serious eye irritation.



Warning, STOT SE 3, May cause drowsiness or dizziness.



Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazard

# SAFETY DATA SHEET

Date : 12/05/2017

Page : 2 / 8

Société : VAR

Nom : Lubricant for chains

## 2.2. Label elements

Symbols:



Danger

Hazard statements:

H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/ doctor/if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Contents:

hexane, reaction mass of isomers (containing < 5 % n-hexane (203-777-6))

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

## 2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards: No other hazards

## 3 - COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

N.A.

### 3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

>= 60% - < 70% hexane, reaction mass of isomers (containing < 5 % n-hexane (203-777-6))

Index number: 601-007-00-7, CAS: 107-83-5, EC: 203-523-4

F,Xn,Xi,N; R11-38-51/53-65-67



2.6/2 Flam. Liq. 2 H225



3.10/1 Asp. Tox. 1 H304

Nom : Lubricant for chains



3.2/2 Skin Irrit. 2 H315



4.1/C2 Aquatic Chronic 2 H411



3.8/3 STOT SE 3 H336

&gt;= 15% - &lt; 20% propane

Index number: 601-003-00-5, CAS: 74-98-6, EC: 200-827-9

F+; R12



2.2/1 Flam. Gas 1 H220



2.5 Press. Gas H280

&gt;= 5% - &lt; 7% butane

Index number: 601-004-00-0, CAS: 106-97-8, EC: 203-448-7

F+; R12



2.2/1 Flam. Gas 1 H220



2.5 Press. Gas H280

&gt;= 3% - &lt; 5% butane

Index number: 601-004-00-0, CAS: 75-28-5, EC: 200-857-2

F+; R12



2.2/1 Flam. Gas 1 H220



2.5 Press. Gas H280

## **4 – FIRST AID MEASURES**

### **4.1. Description of first aid measures**

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

## SAFETY DATA SHEET

Date : 12/05/2017

Page : 4 / 8

Société : VAR

Nom : Lubricant for chains

### **4.2. Most important symptoms and effects, both acute and delayed**

None

### **4.3. Indication of any immediate medical attention and special treatment needed**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment: None

## **5 –FIREFIGHTING MEASURES**

### **5.1. Extinguishing media**

Suitable extinguishing media:

In case of fire, use dust fire extinguisher, CO<sub>2</sub> or foam.

Extinguishing media which must not be used for safety reasons:

None in particular.

### **5.2. Special hazards arising from the substance or mixture**

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

### **5.3. Advice for firefighters**

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

## **6 – ACIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

### **6.2. Environmental precautions**

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

### **6.3. Methods and material for containment and cleaning up**

Wash with plenty of water.

### **6.4. Reference to other sections**

See also section 8 and 13

## **7. HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

### **7.2. Conditions for safe storage, including any incompatibilities**

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

### **7.3. Specific end use(s)**

None in particular

## SAFETY DATA SHEET

Date : 12/05/2017

Page : 5 / 8

Société : VAR

Nom : Lubricant for chains

### **8. EXPOSURE CONTROL/PERSONAL PROTECTION**

#### **8.1. Control parameters**

hexane, reaction mass of isomers (containing < 5 % n-hexane (203-777-6)) - CAS: 107-83-5

ACGIH, 500 ppm, 1000 ppm - Notes: CNS impair, URT and eye irr

butane - CAS: 106-97-8

ACGIH, 1000 ppm - Notes: CNS impair

butane - CAS: 75-28-5

ACGIH, 1000 ppm - Notes: CNS impair

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

#### **8.2. Exposure controls**

Eye protection: Not needed for normal use. Anyway, operate according good working practices.

Protection for skin: Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands: Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Thermal Hazards:None

Environmental exposure controls: None

### **9 – PHYSICAL AND CHEMICAL PROPERTIES**

#### **9.1 Information on basic physical and chemical properties**

Appearance and colour: Liquid limpid colourless

Odour: Odourless

pH: N.A.

Melting point / freezing point: N.A.

Initial boiling point and boiling range: N.A.

Solid/gas flammability: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Flash point: <0 °C

Evaporation rate: N.A.

Vapour pressure: N.A.

Relative density: 0,73 gr/ml c.ca

Solubility in water: Insoluble

Lipid solubility: Total

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Viscosity: N.A.

Explosive properties: N.A.

Oxidizing properties: N.A.

#### **9.2 Other information**

Miscibility: N.A.

Fat Solubility: N.A.

Conductivity: N.A.

Substance Groups relevant properties N.A.

### **10 – STABILITY AND REACTIVITY**

#### **10.1. Reactivity**

It may generate dangerous reactions (See subsections below)

#### **10.2. Chemical stability**

It may generate dangerous reactions (See subsections below)

#### **10.3. Possibility of hazardous reactions**

It may catch fire on contact with oxidising mineral acids.

#### **10.4. Conditions to avoid**

Avoid accumulating electrostatic charge.

#### **10.5. Incompatible materials**

Avoid contact with combustible materials. The product could catch fire.

#### **10.6. Hazardous decomposition products**

None.

# SAFETY DATA SHEET

Date : 12/05/2017

Page : 6 / 8

Société : VAR

Nom : Lubricant for chains

## **11 – TOXICOLOGICAL INFORMATION**

### **11.1. Information on toxicological effects**

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

N.A.

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

## **12 – ECOLOGICAL INFORMATION**

### **12.1. Toxicity**

Adopt good working practices, so that the product is not released into the environment.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**N.A.**

### **12.2. Persistence and degradability**

None

N.A.

### **12.3. Bioaccumulative potential**

N.A.

### **12.4. Mobility in soil**

N.A.

### **12.5. Results of PBT and vPvB assessment**

vPvB Substances: None - PBT Substances: None

### **12.6. Other adverse effects**

None

## **13 – DISPOSAL CONSIDERATION**

### **13.1. Waste treatment methods**

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

## **14- TRANSPORT INFORMATION**

### **14.1 UN number:**

ADR-UN number: 1950

IATA-UN number: 1950

### **14.2 UN proper shipping name:**

ADR-Shipping Name: Aerosol with capacity of 1000 cm<sup>3</sup> Or less

### **14.3 Transport hazard class(es):**

ADR-Class: 2

ADR-Label: UN 1950 Aerosols

IATA-Class: 2.1

IMO-Class: 2.1

### **14.4 Packing Group:**

ADR-Packing Group: III

### **14.5 Environmental hazards**

N.A.

### **14.6 Special Precautions for User**

N.A.

### **14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No

Nom : Lubricant for chains

**15- REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances)

Dir. 99/45/EC (Classification, packaging and labelling of dangerous preparations)

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Dir. 2006/8/EC

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 453/2010 (Annex I)

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

No restriction.

Where applicable, refer to the following regulatory provisions :

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

Provisions related to directives 82/501/EC(Seveso), 96/82/EC(Seveso II): N.A.

**15.2. Chemical safety assessment**

No

**16- OTHER INFORMATION**

Text of phrases referred to under heading 3:

R11 Highly flammable.

R12 Extremely flammable.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R67 Vapours may cause drowsiness and dizziness.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H411 Toxic to aquatic life with long lasting effects.

H336 May cause drowsiness or dizziness.

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

This safety data sheet has been completely updated in compliance to Regulation 453/2010/EU.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

# SAFETY DATA SHEET

Date : 12/05/2017

Page : 8 / 8

Société : VAR

Nom : Lubricant for chains

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.

**DISCLAIMER LIABILITY:** Despite the care of Bring in the drafting of this document No liability can be accepted for damages Case ou accident resulting from the use son. Before USE this product to a request for a new e pour tests, Jun study compatibility DEPTH Materials and A Risk analysis should be Make .The information contained in the present safety data sheet comes from our experience directly. These are good faith All data and corresponding to the present state of our heuristic knowledge about the safety of the products range **VAR®** to date update indicated at the top of page 1. This paper does not in None of the CAS User Knowing and applying all the texts regulating son activity. He will be the only responsible precautions Related to the use of Products range **VAR®**. All regulatory requirements-have mentioned Simply pour aider but the recipient COMPLETE obligations Who obligations of UN LORs use the dangerous or not. This list is not exhaustive Must Be regarded as.